



AT-DI



Tumbler
Dryer

Series 225,325,475 Pound

SPECIFICATION

Standard Features :


- Microprocessor control
- Large capacity slide-out drawer
- Sealed bearings
- Reversing cylinder
- Roller driven cylinder
- Insulated panels
- 24 volt control system
- Rotational sensor

Optional Features :

- Tilt forward
- Tilt both ways
- Variable frequency inverter
- Vertical or horizontal sliding door
- Pass through system with front and rear door
- Side mounted steam coils
- Special design for tunnel washer system
- Humidity control
- PLC control
- Air re-circulating system
- Sprinkler system
- Automatic blower cleaning

MODEL	Metric	US	AT- DI 225	AT- DI 325	AT- DI 475
Maximum Capacity (dry weight)	kg.	lbs.	102(225)	147(325)	215(475)
Overall Dimensions :					
A - Machine Width	mm.	inch	1926 (78.8")	1926(75.8")	3050 (120")
B - Machine Depth	mm.	inch	1550 (61")	1860 (73.2)	3070 (120.87")
C - Machin Height at full	mm.	inch	2902(114.25")	3132(123.3")	3035 (119.49")
D - Machin Height when tilt	mm.	inch	3160 (124.4")	3470 (136.6")	3490 (137.4")
E - Machine Width when tilt	mm.	inch	2075 (81.7")	2335 (92")	3225 (126.97")
Cylinder Information :					
Basket Diameter	mm.	inch	1620 (63.78")	1620 (63.78")	1800 (70.86")
Basket Depth	mm.	inch	1240 (48.8")	1541 (60.70")	2000 (78.74")
Basket Volume	cu.m	cu.ft	2.55 (90.26)	3.17 (112.2)	5.1 (180.1)
Drive Information :					
Basket Motor	kW	HP	2.2(3)	3.7 (5)	5.5(7.5)
Blower Motor	kW	HP	11(15)	15(20)	18.5(25)
Combustion Motor (Gas Model only)	kW	HP	0.25(0.33)	0.25(0.33)	0.37(0.5)
Gas Model :					
Air Flow	cmm	cfm	155 (5500)	184 (6500)	340 (12000)
Gas Consumption	kcal/hr	btu/hr	378000 (1500000)	378000 (1500000)	630000 (2500000)
Gas Inlet Connection	NPT		1-1/2"	1-1/2"	1-1/2"
Exhaust Duct Connection	mm.	inch	508 (20")	508 (20")	609.6 (24")
Net Weight	kg.	lbs.	1664(3668.4)	1837(4050)	3745(8256.3)
Domestic Shipping Weight	kg.	lbs.	1732(3818.4)	1905(4199.8)	3809(8397.4)
Steam Model :					
Air Flow	cmm	cfm	198 (7000)	212 (7500)	340 (12000)
Steam Consumption	kg/hr	lb/hr	469.5(1035)	547.75(1207.5)	939(2070)
Steam Supply Connection	NPT		2"	2"	2"
Steam Return connection	NPT		1-1/4"	1-1/2"	1-1/4"
Exhaust Duct Connection	mm.	inch	508 (20")	508 (20")	610 (24")
Steam Pressure	bar	psi	5.6-8.7(80-125)	5.6-8.79(80-125)	5.6-8.79(80-2125)
Air Pressure	bar	psi	6-8(87-116)	6-8(87-116)	6-8(87-116)
Net Weight	kg.	lbs.	1736(3827.2)	3098(6838)	4720(10405.8)
Domestic Shipping Weight	kg.	lbs.	1800(3968.3)	3234(7129.75)	4885(10769.6)

Specification of design is subject to change without notice. For additional options please consult factory and distributor.



ACCURATE TECHNOLOGIES CO., LTD.

Bangkok, Thailand Phone : +66(0)2740-5511 (Auto) Fax : +66(0)2740-5522, 2740-5533

Website : www accuratethai.com Email : sales@accuratethai.com